



Product Specification

“PT Sari Mas Permai is the first integrated coconut oil plant in Indonesia”



Need more information, please contact us :



address :

**JI Warugunung No 23, Warugunung - Karangpilang
Surabaya 60221, Indonesia**

e-mail :

marketing@sarimas.com

website :

www.sarimas.com

call / phone :

(+62 31) 766 2434

Certificate :





PT. SARI MAS PERMAI

coconut cooking oil company
based in Surabaya, Indonesia

for more information www.sarimas.com

Products

Packagings



RBD Hydrogenated Coconut Oil

RBD Hydrogenated coconut oil is RBD CNO that has gone through a hydrogenation process. RBD HCNO is a solid white fat in texture and a clear liquid if applied to heat. It can be used as the main raw material in food industries.

parameter	Specification	Test Method
FFA as Lauric	0,10 Max	AOCS Ca 5a - 40
Moisture & Impurities	0,10 Max	AOCS Ca 2c - 25
Iodine Value (Wijs)	1,0 Max	AOCS Cd 1 - 25
Colour	1,2 R Max	5,25" Lovibond Cell
Slip Melting Point	30 - 34° Celsius	AOCS Cc 3 - 25
Solid Fat Content		AOCS Cd 16b - 93
	20 C	
	30 C	



Refined, Bleached, and Deodorized Coconut Oil

In order for crude coconut oil to be suitable for consumption, it must be refined, bleached and deodorized (RBD). RBD Coconut Oil is used in coconut-based cooking oil, for food processing commercial and in oleochemical industries.

parameter	Specification	Test Method
FFA as Lauric	0,10 % Max	AOCS Ca 5a - 40
Moisture & Impurities	0,10 % Max	AOCS Ca 2c - 25
Iodine Value (Wijs)	10,50 Max	AOCS Cd 1 - 25
Colour	Red 1,50 Max	5,25" Lovibond Cell



Crude Coconut Oil

Crude Coconut Oil is made from copra which is finely-matured coconut and has dried meat. It must be further processed to be applicable for use in foods, soaps and in the oleochemical industry.

parameter	Specification	Test Method
FFA as Lauric	4,00 % Max	AOCS Ca 5a - 40
Moisture & Impurities	1,00 % Max	AOCS Ca 2c - 25
Iodine Value (Wijs)	10,50 Max	AOCS Cd 1 - 25
Colour	Red 15,00 Max	



Coconut Fatty Acid Distillate

Coconut Fatty Acid Distillate is the side product obtained during the refining process of crude coconut oil. It is mainly used in soap manufacturing industries.

parameter	Specification	Test Method
FFA as Lauric	65,00 % Min	AOCS Ca 5a - 40
Moisture & Impurities	1,00 % Max	AOCS Ca 2c - 25
Iodine Value (Wijs)	15,00 Max	AOCS Cd 1 - 25



Copra Pellets

Copra expellers are made into pellet forms

parameter	Specification	Test Method
Protein	19,00 % Min	AOCS Ba 4a - 38
Moisture	12,00 % Max	AOCS Ca 2c - 25
		PORIM p2.2
Oil	6,00 Max	AOCS Ba 3 - 38



Flexi Bag

Capacity 20 - 21,5 Ton



Drum

Capacity 190 Kg



Tote Bag

Capacity 915 Kg



BIB / Jerrycan

RBD CNO : Capacity 18 Kg
RBD HCNO : Capacity 20 Kg



Our History

Sari Mas Permai started in 1978 as a high quality coconut oil plant with only ten employees that produced up to 5 tons of cooking oil per day. We experienced amazing growth after the first factory was established back in 1985. We've added new machineries and built more refinery facilities that have led to a breakthrough in producing coconut cooking oil in 2000. In 2015, we consistently engaged ourselves in Corporate Social Responsibility programs that focus on giving back to the community and the environment. Now, thanks to your growing trust in us, we are able to expand our growth in the global market as well as in the community.

