

PACE[®]

Prime Series


High Speed Servo Driven VFFS Machine
Intermittent Motion **with Stripping Action**

Quality
Made **A**ffordable...




Prime Series

High Speed Servo Driven VFFS Machine
Intermittent Motion **with Stripping Action**



Pillow Bag



Gusseted Bag

Compact & Rugged Structure

- Frame designed with strong, sturdy & precise components to ensure minimum vibration at optimum machine speed.

Control System

- High end motion CPU loaded with intelligent and interactive software.
- Multiple machines can be connected through MIS / SCADA for remote monitoring.

Operator Interface (HMI)

- Touch controlled color display with user friendly graphical interface.
- Save up to 100 recipe.
- OEE data.

Stripping Action

- Helpful to reduce the product in seal.
- Better nitrogen percentage in pouch.

Real Sealing Time & Controlled Seal Force

- Sealing time remains constant at any given speed.
- Sealing force can be adjusted to meet the sealing requirement of different laminate structures.

Product In Seal Detection

- Auto Product in Seal Detection with tube rejection mechanism

Vacuum Assisted Bag Pulling

- To minimize slippage & smooth bag pulling.

Forming Parts

- Toolless Easy changeover.
- Cross welded hopper with forming tube to reduce the blockage.

Air & Nitrogen Control Panel

- Separate panel for intermittent and continuous nitrogen purging.
- Low pressure detection system.
- Prevent air losses and ensure cut off of air supply when machine is in idle condition.

Film Splicing Plate

- Hold the finished film and provides easy platform to joint the new Roll



India's Leading Brand for
Packaging Machines
with **Turnkey Solutions**

Prime Series

TECHNICAL SPECIFICATION

Machine Specification	P200 Prime	P250 Prime
Technology	Intermittent Motion with Stripping Action	
Bag Width (Min. / Max.)	60-200 mm	60-250 mm
Bag Length (Max.)	275 mm	350 mm
Connecting Load	8 KW / Hr	8 KW / Hr
Air Requirement	3 CFM @ 7 Bar	3 CFM @ 7 Bar
Maximum Film Reel Width	425 mm	525 mm
Maximum Film Reel Diameter	450 mm	450 mm
Core ID	76 mm	76 mm
Maximum Machine MOutput	UPTO 120 BPM	UPTO 120 BPM
Maximum Machine Weight Approx.	800 Kg.	850 Kg.
Dimension L X W X H (mm)	1890 X 950 X 1825	1900 X 1050 X 1890



PACE[®]

PACE PACKAGING MACHINES PVT. LTD.

Plot No. 377A, Road No. 9. G.I.D.C., Kathwada, Ahmedabad - 382 430, Gujarat, INDIA.

☎ +91-98252 66555 | +91-90990 55771 ✉ info@pacepackaging.in