





Vertical Form-Fill-Seal machine



An answer for the pursuit of ideal between Quality and Cost

A New Japan-Basic from Long-established Tokyo Automatic Machinery Works

Enhanced productivity with stable operation

- Max. 100bpm is achieved even with Intermittent motion
- Servo driven and 2-link type heater system for end sealing structure realize a higher seal quality

Easy Operation

- A 5-inch color touch screen with fine viewability
- An easy film change by air-chuck type film reel

Standard Equipment

- Two-stage end-sealing motion
- Vacuum chamber type film tensioning
- Dual servo driven vacuum belts

Options

- Auger Filler
- Punch hole mechanism
- Gus flushing device
- Various types of printers

Servo driven and 2-link type heater system





Machine Specification < TWJB3 >


External Dimensions (mm)

| Bag Type | Pillow, Gusset, Block-bottom gusset, Chain bag | |
|--------------------|--|-------------------------|
| Bag Size | Width | 50 – 220mm |
| | Length | 50 – 300mm |
| Packaging Speed | Max 100 bags/min | |
| Power Supply | 3 Phase 200V 50/60Hz 8.3kVA | |
| Power Consumption | 4.0 kW | |
| Air Consumption | 220 L(Normal)/min | |
| Machine Dimensions | W 1138 mm | x D 1889 mm x H 1413 mm |
| Machine Weight | 620 kg | |

Machine Specification < TWJB8>

| Bag Type | Pillow, Gusset, Block-bottom gusset, Chain bag | |
|--------------------|--|-------------------------|
| Bag Size | Width | 100 – 300mm |
| | Length | 50 – 410mm |
| Packaging Speed | Max 100 bags/min (in case W 120 x L 150) | |
| Power Supply | 3 Phase 200V 50/60Hz 9.8kVA | |
| Power Consumption | 5.6 kW | |
| Air Consumption | 220 L(Normal)/min in 100bpm | |
| Machine Dimensions | W 1426 mm | x D 1944 mm x H 1673 mm |
| Machine Weight | 730 kg | |

*()=TWJB8 *()=TWJB8 463 675 1138(1426)





Tokyo Automatic Machinery Works, Ltd.

TOJIKI BLDG.,3-10-7 Iwamotocho,Chiyoda-Ku,Tokyo 101-0032 Japan TEL: 81-3-3866-4824 FAX: 81-3-3866-7150

URL: http://www.tam-tokyo.co.jp/ E-mail: tam-overseas@tam-tokyo.co.jp