

Tabletop Strapping Machine

Japanese Quality

- Capable of applying very light tension to prevent damage to delicate packages.
- Compatible with soft strapping materials like foam strap, making it ideal for gift packaging.
- Supports anti-static straps, making it suitable for securing semiconductor trays.

TINY-R



Standard Specifications

Dimension	Width	760 mm	29-7/8 in.
	Height	403 mm	15-7/8 in.
	Depth	300 mm	11-7/8 in.
	Weight	22.5 kg	50 lbs.
Arch Size		W 370 x H 180 mm	W 14-1/2 x H 7 in.
Table Height		185 mm	7-1/4 in.
Package Dimensions	Minimum	W 80 x H 30 mm	W 3-1/4 x H 1-1/4 in.
	Maximum	W 340 x H 170 mm	W 13-3/8 x 6-3/4 in.
Joint / Strap / Coil		heat seal / polypropylene or foam ID 100 X OD 150 X W 145 mm	heat seal / polypropylene or foam ID 4 X OD 6 X W 5-3/4 in.
Strap		8 mm	3/8 in.
Strap Tension		38-90 N (3.87-9.17 kgf)	8.5-20 lbf
Power Supply		Single Phase 0.47 kVA	

Dimensions and specifications are subject to change without notice.
Modification rights reserved.

© 2025 Strapack Corporation

DISTRIBUTED BY:



STRAPACK CORPORATION
8-16-6 Ginza, Chuo-ku, Tokyo, 104-0061, JAPAN
(URL) <http://www.strapack.com> (E-mail) info@strapack.com



STRAPACK, N.V./S.A.
Uilenbaan 200, B-2160 Wommelgem, BELGIUM
Phone 32-(0)3-355-1520 Fax. 32-(0)3-355-1521



STRAPACK INC.
21075 Alexander Court, Unit F, Hayward, CA 94545 U.S.A.
Phone 1-510-475-6000 Fax. 1-510-475-6090
101 Industrial Park Road NW, Milledgeville, GA 31061 U.S.A.
Phone 1-478-203-9001 Fax. 1-478-203-9009